

SIMPLE AND SAFE AUDIO LINKS

DOCKING



The modular portable codec for outside broadcast requesting ultra mobility as well as a fully packed commentary unit



AoIP Ethernet / 3G / 4G / 5G / Wi-Fi

3G / 4G / 5G



Docking Station



SIMPLICITY

- + 4 backlit assignable buttons
- + 1 encoder
- + 2 dedicated potentiometers for microphone gain
- + 2 dedicated potentiometers for headphone level (with Tx/Rx balance wheel)
- + 2 dedicated buttons for mic

CONNECTIVITY

- + 1x additional Ethernet
- + 2 additional USB ports
- + GPIO 2x2
- + 1 SFP port (for AES67) and Ethernet

SAFETY

- + Power supply via XLR4
- + ScoopyFlex battery power supply
- + Guide for easy mounting
- + Magnets to hold the assembly

AUDIO INTERFACES


- + Best in class audio pre-amplification
- + 2 additional microphone positions
- + 2 additional stereo headphones
- + 1 AES3 input
- + 2 line outputs
- + 8 channels AES67 interface (RAVENNA or DANTE)



Docking right side



Docking left side



Docking top



Docking back

CODING ALGORITHMS



3G+ / 4G-LTE / 5G / ETHERNET / Wi-Fi
LINEAR, OPUS, AAC-LC/HE/LD, ELD, MPEG L2, G722, G711



3G / 4G *AMR-WB, AMR-NB, VoLTE*

Versions

Feature/ Version	Ethernet	Wifi and bluetooth	Built-in Mobile (3G/4G-LTE/5G)	AES 67	Audio I/O
With Docking station	2x	Yes	Up to 2	8 channels Ravenna or Dante (optional)	INPUTS: 2 mic/line, 2 mic, 1 AES OUTPUTS: 2 line out, 4 headset jacks

AUDIO INTERFACES

MOBILE DEVICE

- + 2 mic/line inputs with phantom power, HP filter, limiter
- + 2 stereo headphone sockets for monitoring, flexible routing and volume control
- + 2x line outputs
- + Redundant Ravenna or Dante interface (up to 8 channels)
 - Ethernet
 - SFP socket

USER INTERFACE

- + Color TFT 5" touchscreen display ultra rugged
- + Rotary encoder and keys
- + Dedicated and assignable backlit pushbuttons (Docking)
- + Easy to use presets

REMOTE CONTROL AND SUPERVISION

- + Transmission of digital I/O (GPIO) : 2 inputs, 2 outputs

NETWORK INTERFACES

- + 1 Ethernet interface, 10BaseT / 100BaseT / 1000BaseT

GENERAL

- + Power: external DC 12V, or Li ion rechargeable battery (autonomy > 5 h), charger included (Mobile Device)
- + Size 178 x 128 x 50 mm (WxDxH)
- + Size of Docking station 185 x 189 x 75 mm (WxDxH)
- + Weight 728g/957g with battery
- + Weight of docking station ~0.850 kg
- + 2x USB host interfaces

OPTIONS

- + Ravenna 8 channels
- + Dante 8 channels
- + Power Over Ethernet (POE)

ACCESSORIES

- + Flight-case
- + XLR4 external power supply

Centre d'affaires La Boursidière, rue de la boursidière
BP82 / F-92357 Le Plessis Robinson - France
Tél. +33 1 41 36 12 00 / Fax +33 1 41 36 12 69

SALES
sales@aeta-audio.com

AFTER SALES SERVICE
aftersales@aeta-audio.com

www.aeta-audio.com